





Deep Freezer Hard Top Units



NWHF225H



EXTERNAL DIMENSIONS
760 (W) x 695 (D) x 840 (H)



INTERNAL DIMENSIONS
630 (W) x 530 (D) x 697 (H)



GROSS VOLUME
232 Liters



NET VOLUME-
211 Liters



No. of Basket
01 no.




INSULATION
60 MM POLYURETHANE



FOOTPRINT AREA
0.52 sq. m



CONTAINER LOAD 20'ft / 40'ft
42 nos. / 84 nos.




TEMPERATURE RANGE
-17°C to -22°C


High Ambient – Hard Top
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant



NWHF325HSD



EXTERNAL DIMENSIONS
1060 (W) x 695 (D) x 840 (H)



INTERNAL DIMENSIONS
930 (W) x 530 (D) x 697 (H)



GROSS VOLUME
343 Liters



NET VOLUME-
311 Liters



No. of Basket
01 no.




INSULATION
60 MM POLYURETHANE



FOOTPRINT AREA
0.73 sq. m



CONTAINER LOAD 20'ft / 40'ft
30 nos. / 64 nos.




TEMPERATURE RANGE
-17°C to -22°C




High Ambient – Hard Top
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant



NWHF425H



EXTERNAL DIMENSIONS
1360 (W) x 695 (D) x 840 (H)



INTERNAL DIMENSIONS
1230 (W) x 530 (D) x 697 (H)



GROSS VOLUME
454 Liters



NET VOLUME-
412 Liters



No. of Basket
02 no.




INSULATION
60 MM POLYURETHANE



FOOTPRINT AREA
0.94 sq. m



CONTAINER LOAD 20'ft / 40'ft
24 nos. / 48 nos.




TEMPERATURE RANGE
-17°C to -22°C


High Ambient – Hard Top
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant



NWHF525H



EXTERNAL DIMENSIONS
1606 (W) x 695 (D) x 840 (H)



INTERNAL DIMENSIONS
1480 (W) x 530 (D) x 697 (H)



GROSS VOLUME
546 Liters



NET VOLUME-
495 Liters



No. of Basket
02 no.




INSULATION
60 MM POLYURETHANE



FOOTPRINT AREA
1.11 sq. m



CONTAINER LOAD 20'ft / 40'ft
20 nos. / 40 nos.




TEMPERATURE RANGE
-17°C to -22°C

High Ambient – Hard Top
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant






NWHF825H



EXTERNAL DIMENSIONS
1657 (W) x 915 (D) x 861 (H)



INTERNAL DIMENSIONS
1530 (W) x 750 (D) x 683 (H)



GROSS VOLUME
783 Liters



NET VOLUME-
726.4 Liters



No. of Basket
02 no.




INSULATION
60 MM POLYURETHANE



FOOTPRINT AREA
1.51 sq. m



CONTAINER LOAD 20'ft / 40'ft
12 nos. / 26 nos.



TEMPERATURE RANGE
-17°C to -22°C


High Ambient – Hard Top
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant




Deep Freezer Glass Top Units



NWHF225G



EXTERNAL DIMENSIONS
760 (W) x 695 (D) x 795 (H)



INTERNAL DIMENSIONS
630 (W) x 530 (D) x 677 (H)



GROSS VOLUME
226 Liters



NET VOLUME-
211 Liters



No. of Basket
01 no.




INSULATION
60 MM POLYURETHANE



FOOTPRINT AREA
0.52 sq. m



CONTAINER LOAD 20'ft / 40'ft
42 nos. / 84 nos.




TEMPERATURE RANGE
-17°C to -22°C


High Ambient – Glass Top | | Low E Coating on Glass
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant



NWHF325G



EXTERNAL DIMENSIONS
1060 (W) x 695 (D) x 795 (H)



INTERNAL DIMENSIONS
930 (W) x 530 (D) x 677 (H)



GROSS VOLUME
333 Liters



NET VOLUME-
311 Liters



No. of Basket
01 no.




INSULATION
60 MM POLYURETHANE



FOOTPRINT AREA
0.73 sq. m



CONTAINER LOAD 20'ft / 40'ft
30 nos. / 64 nos.




TEMPERATURE RANGE
-17°C to -22°C


High Ambient – Glass Top | | Low E Coating on Glass
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant



NWHF425G



EXTERNAL DIMENSIONS
1360 (W) x 695 (D) x 795 (H)



INTERNAL DIMENSIONS
1230 (W) x 530 (D) x 677 (H)



GROSS VOLUME
441 Liters



NET VOLUME-
412 Liters



No. of Basket
02 no.




INSULATION
60 MM POLYURETHANE



FOOTPRINT AREA
0.93 sq. m



CONTAINER LOAD 20'ft / 40'ft
24 nos. / 48 nos.




TEMPERATURE RANGE
-17°C to -22°C




High Ambient – Glass Top | | Low E Coating on Glass
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant



NWHF550G



EXTERNAL DIMENSIONS
1650 (W) x 695 (D) x 855 (H)



INTERNAL DIMENSIONS
1530 (W) x 530 (D) x 722 (H)



GROSS VOLUME
585.5 Liters



NET VOLUME-
553 Liters



No. of Basket
03 no.




INSULATION
60 MM POLYURETHANE



FOOTPRINT AREA
1.07 sq. m



CONTAINER LOAD 20'ft / 40'ft
20 nos. / 40 nos.




TEMPERATURE RANGE
-17°C to -22°C




High Ambient – Glass Top | | Low E Coating on Glass
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant



NWHF825G



EXTERNAL DIMENSIONS
1657 (W) x 915 (D) x 861 (H)



INTERNAL DIMENSIONS
1530 (W) x 750 (D) x 670 (H)



GROSS VOLUME
768.8 Liters



NET VOLUME-
726.4 Liters



No. of Basket
04 no.




INSULATION
60 MM POLYURETHANE



FOOTPRINT AREA
1.51 sq. m



CONTAINER LOAD 20'ft / 40'ft
12 nos. / 26 nos.



TEMPERATURE RANGE
-17°C to -22°C


High Ambient – Glass Top | | Low E Coating on Glass
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant




Deep Freezer Curved Glass Top Units



NWHF225GCL



EXTERNAL DIMENSIONS
756 (W) x 695 (D) x 885 (H)



INTERNAL DIMENSIONS
630 (W) x 530 (D) x 726 (H)



GROSS VOLUME
242 Liters



NET VOLUME-
211 Liters



No. of Basket
01 no.




INSULATION
60 MM POLYURETHANE



FOOTPRINT AREA
0.52 sq. m



CONTAINER LOAD 20'ft / 40'ft
42 nos. / 84 nos.




TEMPERATURE RANGE
-17°C to -22°C


High Ambient – Curve Top | | Low E Coating on Glass
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant



WHF325GCL



EXTERNAL DIMENSIONS
1095 (W) x 644 (D) x 825 (H)



INTERNAL DIMENSIONS
960 (W) x 472 (D) x 698 (H)



GROSS VOLUME
316 Liters



NET VOLUME-
293.0 Liters



No. of Basket
QDI Basket with Mesh -01 no.
Normal Basket – 01 no.




INSULATION
60 MM POLYURETHANE



FOOTPRINT AREA
0.70 sq. m



CONTAINER LOAD 20'ft / 40'ft
30 nos. / 60 nos.



TEMPERATURE RANGE
-17°C to -22°C




High Ambient – Curve Top || Low E Coating on Glass
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant



WHF425GCL




High Ambient – Curve Top || Low E Coating on Glass
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant



EXTERNAL DIMENSIONS

1296 (W) x 644 (D) x 855 (H)



INTERNAL DIMENSIONS

1166 (W) x 472 (D) x 730 (H)



GROSS VOLUME

402 Liters



NET VOLUME-

358.0 Liters



No. of Basket

QDI Basket with Mesh -01 no.
QDI Basket w/o Mesh -01 no.
Normal Basket – 01 no.



INSULATION

60 MM POLYURETHANE




FOOTPRINT AREA

0.83 sq. m



CONTAINER LOAD 20'ft / 40'ft

24 nos. / 48 nos.



TEMPERATURE RANGE


-17°C to -22°C




Deep Freezer Hard Top Eutectic Units



NWHF225HE



EXTERNAL DIMENSIONS
760 (W) x 695 (D) x 840 (H)



INTERNAL DIMENSIONS
590 (W) x 490 (D) x 697 (H)



GROSS VOLUME
201 Liters



NET VOLUME-
182 Liters



No. of Basket
01 no.




INSULATION
80 MM POLYURETHANE



FOOTPRINT AREA
0.52 sq. m



CONTAINER LOAD 20'ft / 40'ft
42 nos. / 84 nos.




TEMPERATURE RANGE
-17°C to -22°C


High Ambient – Eutectic Hard Top
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant



NWHF325HE



EXTERNAL DIMENSIONS
1060 (W) x 695 (D) x 840 (H)



INTERNAL DIMENSIONS
890 (W) x 490 (D) x 670 (H)



GROSS VOLUME
292 Liters



NET VOLUME-
275 Liters



No. of Basket
01 no.




INSULATION
80 MM POLYURETHANE



FOOTPRINT AREA
0.73 sq. m



CONTAINER LOAD 20'ft / 40'ft
30 nos. / 64 nos.




TEMPERATURE RANGE
-17°C to -22°C

High Ambient – Eutectic Hard Top
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant






NWHF425HE



EXTERNAL DIMENSIONS
1360 (W) x 695 (D) x 840 (H)



INTERNAL DIMENSIONS
1190 (W) x 490 (D) x 670 (H)



GROSS VOLUME
390 Liters



NET VOLUME-
368 Liters



No. of Basket
02 no.




INSULATION
80 MM POLYURETHANE



FOOTPRINT AREA
0.94 sq. m



CONTAINER LOAD 20'ft / 40'ft
24 nos. / 48 nos.




TEMPERATURE RANGE
-17°C to -22°C


High Ambient – Eutectic Hard Top
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant



NWHF425HE-2D



EXTERNAL DIMENSIONS
1360 (W) x 695 (D) x 840 (H)



INTERNAL DIMENSIONS
1190 (W) x 490 (D) x 670 (H)



GROSS VOLUME
390 Liters



NET VOLUME-
368 Liters



No. of Basket
NA.




INSULATION
80 MM POLYURETHANE



FOOTPRINT AREA
0.94 sq. m



CONTAINER LOAD 20'ft / 40'ft
24 nos. / 48 nos.




TEMPERATURE RANGE
-17°C to -22°C


High Ambient – Eutectic Hard Top
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant



NWHF525HE-3D



EXTERNAL DIMENSIONS
1606 (W) x 695 (D) x 920 (H)



INTERNAL DIMENSIONS
1440 (W) x 490 (D) x 680 (H)



GROSS VOLUME
480 Liters



NET VOLUME-
446 Liters



No. of Basket
NA.




INSULATION
80 MM POLYURETHANE



FOOTPRINT AREA
1.11 sq. m



CONTAINER LOAD 20'ft / 40'ft
20 nos. / 40 nos.



TEMPERATURE RANGE
-17°C to -22°C


High Ambient – Eutectic Hard Top
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant




Deep Freezer Glass Top Eutectic Units



NWHF425GE



EXTERNAL DIMENSIONS
1355 (W) x 695 (D) x 795 (H)



INTERNAL DIMENSIONS
1190 (W) x 490 (D) x 675 (H)



GROSS VOLUME
393 Liters



NET VOLUME-
368 Liters



No. of Basket
02 no.




INSULATION
80 MM POLYURETHANE



FOOTPRINT AREA
0.94 sq. m



CONTAINER LOAD 20'ft / 40'ft
24 nos. / 48 nos.



TEMPERATURE RANGE
-17°C to -22°C



High Ambient – Glass Top Eutectic
| Low E Coating on Glass | Improved Energy Efficiency | Quiet Compressor | Lock And Key arrangement | Safety Compliant




Deep Freezer Scooping Units



NWHS425G



High Ambient – Scooping Parlour | | Low E Coating on Glass | Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant



EXTERNAL DIMENSIONS

1360 (W) x 695 (D) x 1165 (H)



INTERNAL DIMENSIONS

1230 (W) x 530 (D) x 677 (H)



GROSS VOLUME

441 Liters



NET VOLUME-

412 Liters



No. of Basket

03 no.



INSULATION

60 MM POLYURETHANE




FOOTPRINT AREA

0.93 sq. m



CONTAINER LOAD 20'ft / 40'ft

24 nos. / 48 nos.




TEMPERATURE RANGE

-17°C to -22°C



NWHS550G



EXTERNAL DIMENSIONS

1650 (W) x 695 (D) x 1275 (H)



INTERNAL DIMENSIONS

1530 (W) x 530 (D) x 722 (H)



GROSS VOLUME

585.5 Liters



NET VOLUME-

412 Liters



No. of Basket

04 no.



INSULATION

60 MM POLYURETHANE




FOOTPRINT AREA

1.07 sq. m



CONTAINER LOAD

20'ft / 40'ft




TEMPERATURE RANGE

-17°C to -22°C

High Ambient – Scooping Parlour | | Low E Coating on Glass | Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant



NWHS825G



EXTERNAL DIMENSIONS

1657 (W) x 910 (D) x 1225 (H)



INTERNAL DIMENSIONS

1530 (W) x 750 (D) x 670 (H)



GROSS VOLUME

768 Liters



NET VOLUME-

768 Liters



No. of Basket

04 no.



INSULATION

60 MM POLYURETHANE




FOOTPRINT AREA

1.11 sq. m



CONTAINER LOAD

20'ft / 40'ft



TEMPERATURE RANGE

-17°C to -22°C

High Ambient – Scooping Parlour | | Low E Coating on Glass | Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant




Deep Freezer Freezer on Wheels




WHFG200S



High Ambient – Freezer on Wheels | Low E Coating on Glass | Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant



EXTERNAL DIMENSIONS
940 (W) x 640 (D) x 785 (H)



INTERNAL DIMENSIONS
455 (W) x 455 (D) x 570 (H)



GROSS VOLUME
117 Liters



NET VOLUME-
115 Liters



No. of Basket
NA.




INSULATION
60 MM POLYURETHANE



FOOTPRINT AREA
0.60 sq. m



CONTAINER LOAD 20'ft / 40'ft
32 nos. / 68 nos.




TEMPERATURE RANGE
-18°C to -25°C


WHFG250S



High Ambient – Freezer on Wheels | Low E Coating on Glass | Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant



EXTERNAL DIMENSIONS
940 (W) x 640 (D) x 905 (H)



INTERNAL DIMENSIONS
455 (W) x 455 (D) x 690 (H)



GROSS VOLUME
142 Liters



NET VOLUME-
139 Liters



No. of Basket
NA.




INSULATION
60 MM POLYURETHANE



FOOTPRINT AREA
0.60 sq. m



CONTAINER LOAD 20'ft / 40'ft
32 nos. / 68 nos.




TEMPERATURE RANGE
-18°C to -25°C




WHFG300S



High Ambient – Freezer on Wheels | Low E Coating on Glass | Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Compliant



EXTERNAL DIMENSIONS
990 (W) x 633 (D) x 890 (H)



INTERNAL DIMENSIONS
632 (W) x 480 (D) x 674 (H)



GROSS VOLUME
204.5 Liters



NET VOLUME-
200.2 Liters




No. of Basket
NA.



INSULATION
60 MM POLYURETHANE



FOOTPRINT AREA
0.60 sq. m




TEMPERATURE RANGE
-18°C to -25°C




COMBI UNIT



WHCF425H



EXTERNAL DIMENSIONS
1360 (W) x 695 (D) x 840 (H)



INTERNAL DIMENSIONS
FREEZER CABINET-
562 (W) x 530 (D) x 685 (H)
COOLER CABINET-
562 (W) x 530 (D) x 685 (H)



GROSS VOLUME
FREEZER CABINET – 162.5 Liters
COOLER CABINET – 205 Liters



NET VOLUME
FREEZER CABINET – 146 Liters
COOLER CABINET – 188 Liters



No. of Basket
01 Nos-Freezer Cabinet




INSULATION
60 MM POLYURETHANE



FOOTPRINT AREA
0.94 sq. m



CONTAINER LOAD 20'ft / 40'ft
22 nos. / 46 nos.



TEMPERATURE RANGE
FREEZER CABINET – -17.0°C to 22.0°C
COOLER CABINET – 0.0°C to 10.0°C

High Ambient – Combination Unit
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Complaint




CONVERTIBLE UNIT




NWHD125H



High Ambient – Convertible Unit
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Complaint



EXTERNAL DIMENSIONS
555 (W) x 640 (D) x 880 (H)



INTERNAL DIMENSIONS
430 (W) x 465 (D) x 515 (H)



GROSS VOLUME
103 Liters



NET VOLUME-
96 Liters



No. of Basket
1 no.




INSULATION
80 MM POLYURETHANE



FOOTPRINT AREA
0.36 sq. m



CONTAINER LOAD 20'ft / 40'ft
54 nos. / 108 nos.



TEMPERATURE RANGE

Freezer application : -17.0°C to -22.0°C


Cooler application : 0 to 10°C




NWHD225H



High Ambient – Convertible Unit
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Complaint



EXTERNAL DIMENSIONS
760 (W) x 695 (D) x 840 (H)



INTERNAL DIMENSIONS
630 (W) x 530 (D) x 697 (H)



GROSS VOLUME
232 Liters



NET VOLUME-
211 Liters



No. of Basket
1 no.




INSULATION
80 MM POLYURETHANE



FOOTPRINT AREA
0.52 sq. m




CONTAINER LOAD 20'ft / 40'ft
42 nos. / 84 nos.




TEMPERATURE RANGE
Freezer application : -17.0°C to -22.0°C
Cooler application : 0 to 10°C



NWHD325H



EXTERNAL DIMENSIONS
1060 (W) x 695 (D) x 840 (H)



INTERNAL DIMENSIONS
930 (W) x 530 (D) x 697 (H)



GROSS VOLUME
343 Liters



NET VOLUME-
311 Liters



No. of Basket
1 no.




INSULATION
80 MM POLYURETHANE



FOOTPRINT AREA
0.73 sq. m



CONTAINER LOAD 20'ft / 40'ft
30 nos. / 64 nos.




TEMPERATURE RANGE
Freezer application : -17.0°C to -22.0°C
Cooler application : 0 to 10°C


High Ambient – Convertible Unit
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Complaint



EWHD580H



EXTERNAL DIMENSIONS
1650 (W) x 695 (D) x 895 (H)



INTERNAL DIMENSIONS
1490 (W) x 490 (D) x 715 (H)



GROSS VOLUME
522 Liters



NET VOLUME-
482 Liters



No. of Basket
2 no.




INSULATION
80 MM POLYURETHANE



FOOTPRINT AREA
1.14 sq. m



CONTAINER LOAD 20'ft / 40'ft
20 nos. / 40 nos.



TEMPERATURE RANGE
Freezer application : -17.0°C to -22.0°C
Cooler application : 0 to 10°C



High Ambient – Convertible Unit
Improved Energy Efficiency | Quiet Compressor
Lock And Key arrangement | Safety Complaint



Vertical Freezer

Vertical Freezer



MODEL	SRF60	SRF350	SRF500	SRF900
Gross Volume	60 Liters	332 Liters	465 Liters	762
Dimensions	502 (W) x 545 (D) x 710 (H)	613 (W) x 706 (D) x 1790 (H)	623 (W) x 750 (D) x 2089 (H)	920 (W) x 780 (D) x 2128 (H)
Shelves	1 no.	4 nos.	5 nos.	10 nos.
Temperature	< -17.0°C	< -17.0°C	< -17.0°C	< -17.0°C
Container Loading	40' – 180 nos. (3 stack) 20' – 81 nos. (3 stack)	40' – 51 nos. 20' – 24 nos.	40' – 48 nos. 20' – 24 nos.	40' – 36 20' – 18



Thank You!!!